



“Fluid-Bed drying with high capacities and easy to use drying box”

The BD-300 is designed for drying bigger lots of coated, pelleted or treated seeds. The technical design is basically our BDS drying system but with all advantages of a removable drying box. This gives you the opportunity to load one box while the other box is being dried. The boxes are designed to fit in already existing hot-water treatment plants for wooden boxes.



The drying box will be placed into the machine and is held in place by specially designed clamps. At the beginning of the process the dust extraction hood closes so that all seals are compressed and no air is lost during the drying process. Because the complete frame is placed on load-cells you can monitor the moisture decrease during the complete drying process. Another advantage of this system is that in the beginning of the process the complete box tilts backwards/forwards to have a homogenous fluidisation as soon as possible.

All these features were already tested and designed in our BDS systems. But the biggest advantage of this BD system is the possibility to remove the box from the dryer and use it for transport / rinsing / treatment. The box is built of stainless steel and has special corners to be sure that the complete box is in fluid-bed while drying. The box can also be emptied with standard in use box tipper.

The system is controlled with a PLC and HMI which gives you the opportunity to set drying protocols with several steps (to slow down the fan when seeds get dryer), dry to pre-set weights and even a logging of all data is included.

Specifications

- Steel powder coated frame
- Stainless steel box is included
- Standard with hot-water heat exchanger (several options available)
- Control box with:
 - PLC controlled drying
 - Frequency controlled fan
 - Air temperature in-out and monitoring of Seed temperature
 - Weight controlled drying (with logging)
 - Drying on pre-set protocols
- Pneumatic dust hood to have a closed system while drying



Options

- Air conditioning systems / recirculation systems
- Hot water treatment system
- Extra drying containers

BD-300 Box Drying System

drying



Technical information

Power	3~400 Vac / 50Hz / 16A
Connector	EU standard round connector 5P 16A Pneumatic connection required (6 bar) Internet connection for remote support
Hot Water-Based Air Heating system	70kw / 3.0 m3/hr T-in = 90°C T-out = 70°C
Capacity	300 l/batch maximum
Dimensions	See below
Dust Extraction	Ø300mm / 6500m3/hr to be connected

