

Seed Single Bucket Elevator 60L

Simple seed bucket elevator, easy to use







SE-60L with CSS-400

To make the filling of the CSS-400 Sieve System more simple, we have the Seed Lift available. This simple single bucket elevator can be easily filled with seeds on a low level. It is even easy to empty our standard drying containers in its hopper.





Easy to empty standard dryer container into the seed lift

Optionally we have a Seed Lot Splitter available which can be mounted on the frame of the SE-60L. Whit this system it is possible to split one lot in 4 similar smaller lots (See figure 1).

The seed lift works very simple, and has an automatic valve which will be opened by the system when the hopper is at the emptying place. You press the up button on the control, and the seeds will be transported from the filling position into the emptying position above the CSS-400 or Seed Lot Splitter, and the door of the hopper will be opened. When you press down, the valve will be closed and the Hopper goes to its filling position again.

(a movie is available to see the Seed Lift at work)

SE-60L



Technical information	
Power	230 Vac Single Phase 50Hz
Dimensions	1620x1510x2300 (lxwxh, when connected with Seed Lot Splitter) 2270x1080x2300 (l x w x h, when connected to CSS-400)

The control panel is equipped with:

- Frequency controlled lift motor
- Up/Stop/Down button to operate
- Emergency stop for emergency situations

