# Drumpriming 6x6



### "Simple and straight forward design for drumpriming"

The Drumpriming Quattro System is a simple and straight forward designed drumpriming system for up to 6 drums (3x 6L and 3x 10L). The top doors can be easily opened so that the drums can be put on to the rotating system. After closing the doors, the rotation can be started.



Snelheid

50.0

Act. Temp

16.8

C

**Safety switch** in the door system. As soon as the doors are opened, the rotation will stop automatically to protect the operator for rotating parts.


#### Specifications:

- Easy to use
- Standard drums can be easily exchanged
- Compact system due to design
- Standard delivered with 3x 6L and 3x 10L drum

#### Options

- Sensor controlled rotation
- Heating system with regulation for constant temperature
- Heating/Cooling system
- Stainless Steel drums of 6L
- LED Light with special spectrum





Technical information		
Power	1~230 Vac / 50Hz / 2A	
Connector	EU standard 2-plug	
Capacity	Drum gross 6L	
Dimensions	1650x960x1580mm	



ct. Tem

16.6

Hoopman equipment & engineering b.v. Dinxperlosestraatweg 145, 7122 JP Aalten, The Netherlands www.hoopman-equipment.nl phone +31(0)543 470 496 fax +31(0)543 479 072 info@hoopman-equipment.nl

## **Drumpriming 6x6**







Standard delivered with 3x 6L drum and 3x 10L drum

Standard drum options for the Drumpriming 6x6		
Ø 198 mm * 238 mm (3.6L)	Ø198 mm * 327 mm (6L)	
5 pc. each side	4 pc. each side	
Ø 274 mm * 238 mm (10L)	Ø274 mm * 327 mm (15L)	Ø274 mm * 417 mm (20L)
4 pc. each side	3 pc. each side	2 pc. each side



**Optional stainless steel drum (6L)** Special segmented design for improved seed mixture



Hoopman equipment & engineering b.v. Dinxperlosestraatweg 145, 7122 JP Aalten, The Netherlands www.hoopman-equipment.nl

phone +31(0)543 470 496 fax +31(0)543 479 072 info@hoopman-equipment.nl